# CDRA-5104V2
## 4Ch 5-in-1 DVR

**AHD** | **APPS** | **HDMI OUTPUT**

- Supports live display, as well as recorded playback of full 4MP (2560 x 1440) for all channels

- Auto-detects between AHD, TVI, CVI, 960H and IP cameras

- Utilizes H.264 compression technology

- Camera setup for frame rate and resolution can be set individually or together

- Real time display and recording rates

- AVI and proprietary backup with watermark via USB port

- Supports mobile phone surveillance applications for both Android and iPhone

- Network connectivity utilizing remote client software with support for multi-site viewing and network backup

- HDMI, VGA and BNC Spot Monitor outputs

- RS485 PTZ Control and UTC Control

- 4 alarm inputs / 1 alarm output

- 1 audio channel

**4 CH** | **MOTION DETECTION** | **960H** | **CMS** | **H.264 COMPRESSION** | **E-MAIL NOTIFICATION**

## Contact your Crest Representative today to learn more about this product!

**Video Security Since 1974**

**CREST ELECTRONICS INC**

*Rear View

| Model Number | CDRA-5104V2 |
|---|---|
| Performance | AHD / TVI / CVI/ IP / Analog \| Pentaplex |
| Video Compression | H.264 |
| Video Inputs | 4 (BNC) / 1 (Network) |
| Video Output | 1 HDMI, 1 VGA, 1 SPOTOUT (BNC) |
| Audio Inputs | 1 (RCA) |
| Audio Output | 1 (RCA) |
| Network Throughput | 60Mbps |
| Recording Frame Rate | 4 * 4MP (24fps) / 4* 3MP (32fps) / 4 * 1080p (60fps) 4 * 720p (120fps) / 4 * 960H (120fps) |
| Recording Resolution | Up to 4MP (2560 x 1440) |
| Recording Modes | Manual, Motion, Schedule |
| Recording Schedule | By Hour / Day & Channel |
| Display Screens | 1, 4 & 5 (1 IP) |
| HDD Capacity | 1 HDD / Up to 10TB |
| Backup Media | USB |
| Alarm / Relay | 4 / 1 |
| PTZ Control | RS485 and UTC Support |
| Network Supported Type | TCP/IP (Dynamic IP Support), DHCP, DDNS |
| Network Software | Remote Client, Smart Phone App |
| Network Audio | Live, Playback, Two Way Network Audio |
| System Control | USB Mouse |
| System | Watchdog System Auto Recovery |
| Dimensions | 10" (W) x 1 3/4" (H) x 7" (D) |
| Power | 12vDC / 2 Amp |

*Specifications subject to change*