

# CJ-23D-N

## Hi-Res Color IP Camera




- Multiple user selectable resolution settings, up to 720 x 480
- 0.6 lux minimum illumination with F1.2 lens
- CS lens mount
- Supports DC-style auto iris lenses
- Built-in web server
- Operates on 12vDC or PoE – user selectable
- Supports static & dynamic IP addresses
- 10/100 base T Ethernet connection (RJ-45)
- Includes analog video output (BNC)
- Includes easy-to-use installation software with auto detect feature
- Utilizes M-JPEG or MPEG-4 (user selectable), for high quality streaming video
- Adjustable bandwidth throttle, allows camera performance to be tailored to the network's capabilities

 **CREST**  
ELECTRONICS INC

**Video Security Since 1974**

# Product Data: CJ-23D-N Hi-Res Color IP Camera



Rear Panel

<b>Model Number</b>	<b>CJ-23D-N</b>
<b>Product Description</b>	Hi-Res Color IP Camera
<b>Pick-Up Elements</b>	771(h) x 492(v) 1/3" Super HAD CCD
<b>Resolution</b>	520 TV Lines Composite Output
<b>Minimum Illumination</b>	0.6 Lux @ F1.2
<b>Lens Mount</b>	CS Mount
<b>Auto Iris</b>	Video / DC Drive
<b>White Balance</b>	ATW / AWC
<b>Backlight Compensation</b>	On/Off Selectable
<b>Gain Control</b>	On/Off Selectable
<b>Motorized IR Cut Filter</b>	N/A
<b>Analog Video Output</b>	BNC
<b>Operating Temperature</b>	14°F ~ 131°F
<b>Power Source</b>	12vDC, 400ma, or PoE, Selectable
<b>Dimensions</b>	2 3/8"W x 2 1/4"H x 3 1/2"D
<b>Housing</b>	Extruded Aluminum
<b>Hardware</b>	32 Bit RISC Processor
<b>Operating System</b>	Embedded Linux
<b>Flash Memory</b>	8 MB
<b>Protocol</b>	TCP/IP, DDNS
<b>Interface</b>	10/100 Base T Ethernet (RJ-45)
<b>Compression</b>	M-JPEG or MPEG-4, Selectable
<b>Resolutions</b>	320x240, 720x480
<b>Frame Rate</b>	30 FPS (720x480)
<b>Video Streaming</b>	CBR, VBR, Adjustable Bit Rate

CJ-23D-N	
Hi-Res Color IP Camera	
CAMERA	
Pick-Up Elements	771(h) x 492(v) 1/3" Super HAD CCD
Resolution	520 TV Lines Composite Output
Minimum Illumination	0.6 Lux @ F1.2
Lens Mount	CS Mount
Auto Iris	Video / DC Drive
White Balance	ATW / AWC
Backlight Compensation	On/Off Selectable
Gain Control	On/Off Selectable
Motorized IR Cut Filter	N/A
Analog Video Output	BNC
Operating Temperature	14°F ~ 131°F
Power Source	12vDC, 400ma, or PoE, Selectable
Dimensions	2 3/8"W x 2 1/4"H x 3 1/2"D
Housing	Extruded Aluminum
NETWORK	
Hardware	32 Bit RISC Processor
Operating System	Embedded Linux
Flash Memory	8 MB
Protocol	TCP/IP, DDNS
Interface	10/100 Base T Ethernet (RJ-45)
Compression	M-JPEG or MPEG-4, Selectable
Resolutions	320x240, 720x480
Frame Rate	30 FPS (720x480)
Video Streaming	CBR, VBR, Adjustable Bit Rate

Specifications subject to change

