

CJ-2907WS-42

Analog Outdoor IR Bullet



750TVL D-WDR with IR and 2.8-12mm Varifocal Lens

- ☞ New 960H chipset for unsurpassed picture clarity
- ☞ IP66 rated weatherproof housing
- ☞ D-WDR technology for great low-light performance
- ☞ True day/night performance, utilizing a motorized IR cut filter
- ☞ 0 lux with IR LEDs on
- ☞ 42 IR LED built-in array with smart IR LED control for IR projection up to 120 feet
- ☞ OSD menu for easy set-up with cable mounted mini-controller
- ☞ 3-axis internal gimbal mount for easy installation on any surface
- ☞ Split glass technology – eliminates IR reflection
- ☞ 12vDC operation
- ☞ Integral sunshield
- ☞ With mount and sunshield:
3 1/2" (width) x 3 3/4" (height) x 10 1/2" (length)




Contact your Crest Representative today
to learn more about this product!




Video Security Since 1974

Product Data: CJ-2907WS-42 Analog Outdoor IR Bullet

Front View



Side View



Model Number
Product Description
Image Pick-Up Device
Certifications
Horizontal Resolution
Minimum Illumination
S/N Ratio
Auto Electronic Shutter
Auto Gain Control
Auto White Balance
Backlight Compensation
Scanning System
Gamma Characteristic
Lens Furnished
Synchronous System
Video Output
Infrared Luminary
Wave Length
Projection Distance
Power Supply
Power Consumption
Operating Temperature
Dimensions

CJ-2907WS-42	
Outdoor 960H WDR Infrared Camera	
High Res 1/3" CCD 960H Image Sensor	
IP66	
750 TV Lines (Color); 800 TV Lines (B/W)	
0 Lux (IR LED on)	
More than 52dB (AGC off)	
NTSC: 1/60-1/100,000s; User Selectable	
Yes	
Yes (2500-9500K)	
Auto / Manual	
Single Scan	
0.45	
2.8-12mm Vari-Focal IR Lens	
Internal	
1 Vp-p / 75 ohms, BNC Connector	
42 Pieces; Smart LED	
850nm	
120 feet max	
DC 12v +/-10%	
800mA min (Camera+IR LED on)	
12 ~ 122°F	
3 1/2"W x 3 3/4"H x 10 1/2"L (with mount and sunshield)	

Specifications subject to change

