



# CP-79MS-70 Enviro Dual Chip Infrared Camera




- ☞ 1/3" super high resolution CCD
- ☞ 520 TVL color; 550 TVL B/W
- ☞ Externally adjustable 2.8 to 11mm vari-focal auto iris lens
- ☞ Built-in 70pc LED array for viewing out to 60 meters
- ☞ Dual voltage – 24vAC / 12vDC
- ☞ Weatherproof housing (IP-66)
- ☞ Dual chip technology
- ☞ Removable sunshield and mount

**CREST**  
ELECTRONICS INC  
Video Security Since 1974

# Product Data: CP-79MS-70 Enviro Dual Chip Infrared Camera



Front View



Side View

<b>Model Number</b>	<b>CP-79MS-70</b>
<b>Product Description</b>	Color / B/W Dual Chip Infrared Camera
<b>Image Pick-Up Device</b>	1/3" CCD Sony Super HAD
<b>Horizontal Resolution</b>	520 Lines Color; 550 Lines B/W
<b>Minimum Illumination</b>	0 Lux @ F2.0, IR On
<b>S/N Ratio</b>	More than 50dB
<b>Auto Electronic Shutter</b>	NTSC: 1/60-1/120,000s
<b>Auto Gain Control</b>	On / Off Selectable
<b>Auto White Balance</b>	ATW / AWC / Manual, Selectable
<b>Scanning System</b>	Interlace 2:1
<b>Gamma Characteristic</b>	0.45
<b>Lens Furnished</b>	2.8-11mm Vari Focal Auto Iris
<b>Synchronous System</b>	Internal, negative sync
<b>Video Output</b>	1 Vp-p / 75 ohms, BNC connector
<b>Infrared Luminary</b>	70 pieces IR LED; Life: 6000 hrs
<b>Wave Length</b>	850nm
<b>OSD</b>	Built-in
<b>Projection Distance</b>	Up to 60 meters
<b>Auto Power ON/OFF</b>	Cds auto control
<b>Illumination Active Limit</b>	Under 10 lux
<b>Power Supply</b>	AC 24v +/-10%; DC 12v +/-10%
<b>Power Consumption</b>	1.2 amp (IR LED ON + Camera)
<b>Operating Temperature</b>	14 ~ 122°F
<b>Dimensions</b>	4 1/8" Dia x 9"L

<b>Model Number</b>	<b>CP-79MS-70</b>
<b>Product Description</b>	Color / B/W Dual Chip Infrared Camera
<b>Image Pick-Up Device</b>	1/3" CCD Sony Super HAD
<b>Horizontal Resolution</b>	520 Lines Color; 550 Lines B/W
<b>Minimum Illumination</b>	0 Lux @ F2.0, IR On
<b>S/N Ratio</b>	More than 50dB
<b>Auto Electronic Shutter</b>	NTSC: 1/60-1/120,000s
<b>Auto Gain Control</b>	On / Off Selectable
<b>Auto White Balance</b>	ATW / AWC / Manual, Selectable
<b>Scanning System</b>	Interlace 2:1
<b>Gamma Characteristic</b>	0.45
<b>Lens Furnished</b>	2.8-11mm Vari Focal Auto Iris
<b>Synchronous System</b>	Internal, negative sync
<b>Video Output</b>	1 Vp-p / 75 ohms, BNC connector
<b>Infrared Luminary</b>	70 pieces IR LED; Life: 6000 hrs
<b>Wave Length</b>	850nm
<b>OSD</b>	Built-in
<b>Projection Distance</b>	Up to 60 meters
<b>Auto Power ON/OFF</b>	Cds auto control
<b>Illumination Active Limit</b>	Under 10 lux
<b>Power Supply</b>	AC 24v +/-10%; DC 12v +/-10%
<b>Power Consumption</b>	1.2 amp (IR LED ON + Camera)
<b>Operating Temperature</b>	14 ~ 122°F
<b>Dimensions</b>	4 1/8" Dia x 9"L

Specifications subject to change

