

CC-4807XS-21

Extreme WDR Analog Vandal Dome



720TVL 960H+ with IR and 2.8-12mm Varifocal Lens

- 👉 Latest Sony Effio-V technology, eliminates glare from bright light (sunlight) while maintaining unsurpassed image quality – great for windows and glass door applications
- 👉 IP66 rated weatherproof housing
- 👉 WDR technology for great performance in all lighting
- 👉 True day/night performance, utilizing a motorized IR cut filter
- 👉 0 lux with IR LEDs on
- 👉 21 IR LED built-in array with smart IR LED control for IR projection up to 65 feet
- 👉 OSD menu with cable-mounted joystick
- 👉 3-axis internal gimbal mount for easy installation on a wall or ceiling
- 👉 12vDC or 24vAC dual voltage
- 👉 5 3/4" (diameter) x 4 1/4" (height)



Optional Accessories:



CHM-4810
Wall Mount



CHM-4810PA
Pole Mount / Corner Mount
Adapter for CHM-4810



CHM-2800
Environmental Wall Mount



CTL-201
OSD Controller

Contact your Crest Representative today to learn more about this product!



Product Data: CC-4807XS-21 Extreme WDR Analog Vandal Dome

	CC-4807XS-21
Model Number	CC-4807XS-21
Product Description	Sony Effio-V Powered 960H+ IR Vandal Dome
Image Pick-Up Device	1/3" Sony Super HAD CCD II Effio V (960H WDR)
Horizontal Resolution	720 TV Lines
Minimum Illumination	0.001 Lux in Color; 0 Lux with IR On
S/N Ratio	More than 52dB
Auto Electronic Shutter	NTSC: 1/60-1/100,000s
Auto Gain Control	User Selectable
Auto White Balance	User Selectable
Back Light Compensation	User Selectable
Scanning System	2:1 Interlace
Gamma Characteristic	0.45
Lens Furnished	2.8-12mm Varifocal Lens DC Auto Iris
Synchronous System	Internal, Negative Sync
Video Output	1 Vp-p / 75 Ohms, BNC Connector
Infrared Luminary	21 pieces Smart IR LED
Wave Length	850nm
Projection Distance	Up to 65 feet
Day/Night Activation	User Selectable
Sense Up	Auto / Off
Power Supply	12vDC +/-10% / 24vAC Dual Voltage
Power Consumption	500mA with LED On
Operating Temperature	14 ~ 122°F
Dimensions	5 3/4" (dia) x 4 1/4" (h)

Specifications subject to change

