

# CC-7907XU-40

## Extreme WDR Analog IR Bullet Cam



### 720TVL 960H+ with IR and 6-22mm Varifocal Lens

- Latest Sony Effio-V technology – eliminates glare from bright light (sunlight) while maintaining unsurpassed image quality. Great for license plates, windows and glass door applications
- IP66 rated weatherproof housing
- WDR technology for great performance in all lighting
- True day/night performance, utilizing a motorized IR cut filter
- 0 lux with IR LEDs on
- 42 IR LED built-in array with smart IR LED control for IR projection up to 130 feet
- OSD menu for easy set-up via cable-mounted joystick
- 3-axis gimbal bracket, allows camera to be mounted to any surface, at any angle
- Split glass technology – eliminates IR reflection
- 3 1/4" (width) x 3" (height) x 9 3/4" (length)



#### Optional Accessories:

CTL-201  
OSD Controller



Contact your Crest Representative today to learn more about this product!



# Product Data: CC-7907XU-40 Extreme WDR Analog IR Bullet Cam

<b>Model Number</b>	<b>CC-7907XU-40</b>
<b>Product Description</b>	Sony Effio-V Powered 960H+ IR Bullet Camera
<b>Image Pick-Up Device</b>	1/3" Sony Super HAD CCD II Effio V (960H WDR)
<b>Horizontal Resolution</b>	720 TV Lines
<b>Minimum Illumination</b>	0.001 Lux in color; 0 Lux with IR LED on
<b>S/N Ratio</b>	More than 52dB
<b>Auto Electronic Shutter</b>	NTSC: 1/60-1/100,000s
<b>Auto Gain Control</b>	User Selectable
<b>Auto White Balance</b>	User Selectable
<b>Backlight Compensation</b>	User Selectable
<b>Scanning System</b>	2:1 Interlace
<b>Gamma Characteristic</b>	0.45
<b>Lens Furnished</b>	6-22mm Varifocal Auto Iris
<b>Synchronous System</b>	Internal; Negative Polarity
<b>Video Output</b>	1 Vp-p / 75 Ohms, BNC Connector
<b>Infrared Luminary</b>	42 pieces smart IR LED
<b>Wave Length</b>	850nm
<b>OSD</b>	Yes
<b>Projection Distance</b>	Up to 130 feet
<b>Day / Night Activation</b>	User Selectable
<b>Power Supply</b>	24vAC; 12vDC +/-10%
<b>Power Consumption</b>	500mA with IR LED on
<b>Operating Temperature</b>	14 ~ 122°F
<b>Dimensions</b>	3 1/4"W x 3"H x 9 3/4"L

*Specifications subject to change*

