

CCN-4840S-21

Megapixel HD IP Vandal Dome



4 Megapixel with IR and 2.8-12mm Varifocal Lens

- Support WEB configuration, and IE network monitoring
- Support dual-stream
- True day/night performance, utilizing a motorized IR cut filter
- 0 lux with IR LEDs on
- 30 IR LED built-in array with smart IR LED control for IR projection up to 82 feet
- Support OSD, color, brightness, saturation and digital zoom
- Ultra-low illumination and high-performance real-time screen, support ABLC image effect
- 12vDC +/-5%, PoE 802.3af
- 5 1/2" (diameter) x 4 3/8" (height)
- Support protocols: TCP/IP, HTTP, DHCP, FTP, DNS, DDNS, RTSP, NTP, SMTP



Contact your Crest Representative today to learn more about this product!



Product Data: CCN-4840S-21 Megapixel HD IP Vandal Dome

Model Number	CCA-4840S-21
Product Description	HD 4MP Vandal Proof IP Dome
Image Pick-Up Device	1/3" 4.0MP OmniVision CMOS
Video Compression	H.264 / JPEG
Minimum Illumination	0 Lux with IR On
S/N Ratio	More than 52dB
Auto Electronic Shutter	NTSC: 1-1/10,000s (adjustable)
Bit Rate	64-12,000Kbps
Max Image Size	2560 x 1440
Back Light Compensation	Support
Frame Rate	60Hz 20FPS @ 4MP / 25FPS @ 1080p
Lens Interface Type	C / CS Mount
Lens Furnished	2.8-12mm Varifocal Lens DC Auto Iris
Storage Function	FTP, Local, NVR, SMTP
Onvif	Onvif 2.4
Infrared Luminary	30 pieces Smart IR LED
Wave Length	850nm
Projection Distance	Up to 82 feet
Day/Night Activation	User Selectable
Communication Interface	RJ45 (10M / 100M) Adaptive Ethernet Port
Power Supply	12vDC +/-5%, PoE (802.3af)
Power Consumption	500mA with IR LED On
Operating Temperature	14 ~ 122°F
Dimensions	5 1/2" (Dia) x 4 3/8" (H)

Specifications subject to change

