

# CCN-7940S-40

## Megapixel HD IP Bullet Camera



### 4 Megapixel with IR and 2.8-12mm Varifocal Lens

- Support WEB configuration, and IE network monitoring
- Support dual-stream
- True day/night performance, utilizing a motorized IR cut filter
- 0 lux with IR LEDs on
- 42 IR LED built-in array with smart IR LED control for IR projection up to 131 feet
- Support OSD, color, brightness, saturation and digital zoom
- Ultra-low illumination and high-performance real-time screen, support ABLC image effect
- 12vDC +/-5%, PoE 802.3af
- 3 5/8" (width) x 3 1/2" (height) x 11 1/2" (length)
- Support protocols: TCP/IP, HTTP, DHCP, FTP, DNS, DDNS, RTSP, NTP, SMTP



Contact your Crest Representative today to learn more about this product!



# Product Data: CCN-7940S-40 Megapixel HD IP Bullet Camera

<b>Model Number</b>	<b>CCA-7940S-40</b>
<b>Product Description</b>	HD 4MP IP Bullet Camera
<b>Image Pick-Up Device</b>	1/3" 4.0MP OmniVision CMOS
<b>Video Compression</b>	H.264 / JPEG
<b>Minimum Illumination</b>	0 Lux with IR On
<b>S/N Ratio</b>	More than 52dB
<b>Auto Electronic Shutter</b>	NTSC: 1-1/10,000s (adjustable)
<b>Bit Rate</b>	64-12,000Kbps
<b>Max Image Size</b>	2560 x 1440
<b>Back Light Compensation</b>	Support
<b>Frame Rate</b>	60Hz 20FPS @ 4MP / 25FPS @ 1080p
<b>Lens Interface Type</b>	C / CS Mount
<b>Lens Furnished</b>	2.8-12mm Varifocal Lens DC Auto Iris
<b>Storage Function</b>	FTP, Local, NVR, SMTP
<b>Onvif</b>	Onvif 2.4
<b>Infrared Luminary</b>	42 pieces Smart IR LED
<b>Wave Length</b>	850nm
<b>Projection Distance</b>	Up to 131 feet
<b>Day/Night Activation</b>	User Selectable
<b>Communication Interface</b>	RJ45 (10M / 100M) Adaptive Ethernet Port
<b>Power Supply</b>	12vDC +/-5%, PoE (802.3af)
<b>Power Consumption</b>	1A with IR LED On
<b>Operating Temperature</b>	14 ~ 122°F
<b>Dimensions</b>	3 3/8" (W) x 3 1/2" (H) x 11 1/2" (L)

*Specifications subject to change*

