

CDP-1212DE

Hi-Speed True Day/Night Color PTZ Dome



- 4" full-feature PTZ dome
- Vandal resistant aluminum, weatherproof body with polycarbonate lower dome
- 1/4" Interline transfer CCD with greater than 600 TV lines
- 12x optical zoom, with 10x digital for 120x total zoom capability
- 127 presets, with up to 8 selectable group tours (up to 20 individual presets each)
- Variable speed pan & tilt motors (360 degrees/sec max.)
- Works with popular control protocols
- Convenient 12vDC operation
- Motorized ICR for true day/night performance



Video Security Since 1974

Product Data: CDP-1212DE Hi-Speed TDN Color PTZ Dome

Model Number		CDP-1212DE (12x Zoom)
Mechanical	Pan Rotation Angle	360° Endless
	Pan Speed	0 ~ 360° / Sec.
	Tilt Rotation Angle	0 ~ 90° (Hardware Autoflip)
	Tilt Speed	0 ~ 360° / Sec.
Functions	Presets	127 positions with a 10 character label available for each position with different speed steps
	Group Tour	Max 8 Programmable Group Tours (each one consisting of up to 20 preset steps)
	Auto Scan	8 Programmable Auto Scan
	Privacy Masking Zones	4 Privacy Zones
	Alarm Actions	Home Activate Preset, Group Scanning or Output Per Alarm Input
	Auto Flip	On / Off
	OSD Menu	Multiple Languages On Screen
	Communication	RS-485
	Protocol	Pelco P / D / Auto
Electrical	Power Consumption	12vDC / 0.8 Amp
	Alarm Input	2 Alarm (NC / NO)
Construction	Dimensions	6 1/2" D x 6 1/4" H x 4" Dia Lower Dome
	Weight	2 Lbs, 6 Oz
	Operating Temperature	0°F ~ 122°F (Indoor)
Camera Module	Image Sensor	1/4" Interline Transfer CCD
	Number of Effective Pixels (NTSC)	768 H x 494 V, 380K
	Horizontal Resolution	More than 600 TV Lines
	Lens	Optical
		Digital
		12x Optical Zoom (F1.6, F=3.4 - 44.4mm)
		10x (120x with Optical)
	Digital Slow Shutter	On / Off
	Min. Illumination	1.0 Lux Color @ F1.8 (50IRE); 0.1 Lux B/W @ F1.8 (50IRE)
	Luminance S/N Ratio	50dB AGC Off
	BLC	Low / Middle / High / Off
	Flickerless Mode	On / Off Selectable
	White Balance	Auto / Manual

Specifications subject to change



Video Security Since 1974