

# CP-48HS-N

## Hi-Def Environmental Vandal Dome



- Utilizes state-of-the-art video compression engine – allows real time streaming of true 720p high definition video
- Triple codec – allows simultaneous streaming of three independent video streams, including H.264, MPEG4 and MJPEG, all with individual settings and requirements
- Operates with IPv4 and IPv6 protocols
- Vari-focal 2.8-11mm auto iris lens
- Operates on 12vDC or PoE – auto selectable
- Composite video output, for use with test monitor
- Digital image stabilization
- Camera is vandal proof and IP-66 weather proof rated
- Includes easy-to-use installation software with auto detect feature



**Video Security Since 1974**

# Product Data: CP-48HS-N Hi-Def Environmental Vandal Dome

Model Number	CP-48HS-N
Product Description	Hi-Def WDR Environmental Vandal Dome
	<b>CAMERA</b>
Pick-Up Elements	1/3" Sony 1.3 MPX CMOS
Resolution	720p
Minimum Illumination	4.7 Lux Color; 0.1 Lux B/W
Lens	2.8 ~ 11mm Vari-Focal Auto Iris
Auto Iris	DC Drive
White Balance	ATW / AWC
WDR Level	Up to x128, User Selectable
Gain Control	Automatic
Motorized IR Cut Filter	On/Off/Auto Selectable
Analog Video Output	BNC
Operating Temperature	14°F ~ 131°F
Power Source	12vDC, 800ma, or PoE, Selectable
Dimensions	5 3/4"Dia x 4 7/8"H
Housing	Aluminum Body, Polycarbonate Lower Dome
	<b>NETWORK</b>
Hardware	32 Bit RISC Processor
Operating System	Embedded Linux
Flash Memory	5 DHC Memory Card
Protocol	TCP/IP, DDNS
Interface	10/100 Base T Ethernet (RJ-45)
Compression	M-JPEG or MPEG-4, H.264
Resolutions	CIF, D1, 720p
Frame Rate	30 FPS (720p)
Video Streaming	CBR, VBR, Adjustable Bit Rate

*Specifications subject to change*

