

CP-79HT-42-N

Full HD IP Enviro IR Bullet Camera



- Utilizes state-of-the-art video compression engine – allows real time streaming of true 1080p high definition video
- Triple codec – allows simultaneous streaming of three independent video streams, including H.264, MPEG4 and MJPEG, all with individual settings and requirements
- Operates with IPv4, IPv6 and DDNS protocols
- Vari-focal 3.6-16mm auto iris lens
- Operates on 12vDC or PoE – auto selectable
- Digital image stabilization
- Camera is IP-67 weather proof rated
- Motorized ICR for true day/night performance
- Built-in 42 LED IR array for illumination out to 150 feet



Video Security Since 1974

Product Data: CP-79HT-42-N Full HD IP Enviro IR Bullet Camera

Model Number	CP-79HT-42-N
Product Description	Full Hi-Def IP Outdoor IR Bullet Camera
	CAMERA
Pick-Up Elements	1/3" Sony 2.0 MPX CMOS
Resolution	1080p, 720p, D1, CIF
Minimum Illumination	0.1 Lux Color; 0.01 Lux B/W (IR Off)
Lens	3.6 ~ 16mm Vari-Focal Auto Iris
Auto Iris	DC Drive
White Balance	ATW / AWC
WDR Level	Up to x128, User Selectable
Gain Control	Automatic
Motorized IR Cut Filter	On/Off/Auto Selectable
Analog Video Output	BNC
Operating Temperature	14°F ~ 131°F
Power Source	12vDC, 1.4 Amp, or PoE, Selectable
Dimensions	3 1/2"W x 3 3/8"H x 12 3/8"L
Infrared Illuminary	42 Pieces; Life 6000 Hrs
Projection Distance	Up to 150 feet
Housing	Aluminum Body
	NETWORK
Hardware	32 Bit RISC Processor
Operating System	Embedded Linux
Flash Memory	5 DHC Memory Card
Protocol	TCP/IP, DDNS
Interface	10/100 Base T Ethernet (RJ-45)
Compression	H.264, MPEG-4 or M-JPEG
Resolutions	CIF, D1, 720p, 1080p
Frame Rate	30 FPS (1080p)

Specifications subject to change

