

CP-95P-N Super Hi-Res Pixim[®] IP Camera



- Multiple user selectable resolution settings, up to 720 x 480
- Featuring Pixim's Digital Pixel System[®] technology
- 0.02 lux in B/W mode
- CS lens mount
- Supports DC style auto iris lenses
- Built-in web server
- Operates on 12vDC or PoE – user selectable
- Supports static & dynamic IP addresses
- 10/100 base T Ethernet connection (RJ-45)
- Includes analog video output (BNC)
- Includes easy-to-use installation software with auto detect feature
- Utilizes M-JPEG or MPEG-4 (user selectable) for high quality streaming video
- Adjustable bandwidth throttle, allows camera performance to be tailored to the network's capabilities


DIGITAL
PIXEL
SYSTEM
FROM PIXIM



 **CREST**
ELECTRONICS INC

Video Security Since 1974

Product Data: CP-95P-N Super Hi-Res Pixim® IP Camera



Rear Panel

Model Number	CP-95P-N
Product Description	Super Hi-Res Pixim® IP Camera
Pick-Up Elements	771(h) x 492(v) 1/3" Pixim® CCD
Resolution	480 TV Lines Composite Output
Minimum Illumination	0.08 Lux Color @ F1.2; 0.02 Lux B/W @ F1.2
Lens Mount	CS Mount
Auto Iris	Video / DC Drive
White Balance	ATW / AWC
Backlight Compensation	On/Off Selectable
Gain Control	On/Off Selectable
Motorized IR Cut Filter	On/Off Selectable
Analog Video Output	BNC
Operating Temperature	14°F ~ 131°F
Power Source	12vDC, 600ma, or PoE, Selectable
Dimensions	2 3/8"W x 2 1/4"H x 3 1/2"D
Housing	Extruded Aluminum
Hardware	32 Bit RISC Processor
Operating System	Embedded Linux
Flash Memory	8 MB
Protocol	TCP/IP, DDNS
Interface	10/100 Base T Ethernet (RJ-45)
Compression	M-JPEG or MPEG-4, Selectable
Resolutions	320x240, 720x480
Frame Rate	30 FPS (720x480)
Video Streaming	CBR, VBR, Adjustable Bit Rate

CP-95P-N	
Super Hi-Res Pixim® IP Camera	
CAMERA	
771(h) x 492(v) 1/3" Pixim® CCD	
480 TV Lines Composite Output	
0.08 Lux Color @ F1.2; 0.02 Lux B/W @ F1.2	
CS Mount	
Video / DC Drive	
ATW / AWC	
On/Off Selectable	
On/Off Selectable	
On/Off Selectable	
BNC	
14°F ~ 131°F	
12vDC, 600ma, or PoE, Selectable	
2 3/8"W x 2 1/4"H x 3 1/2"D	
Extruded Aluminum	
NETWORK	
32 Bit RISC Processor	
Embedded Linux	
8 MB	
TCP/IP, DDNS	
10/100 Base T Ethernet (RJ-45)	
M-JPEG or MPEG-4, Selectable	
320x240, 720x480	
30 FPS (720x480)	
CBR, VBR, Adjustable Bit Rate	

Specifications subject to change

